


NOTES:

- 1. THE CITY OF ST. CHARLES ALLOWS RESIDENTS TO CONNECT SUMP PUMP DISCHARGE LINES TO THE PUBLIC STORM SEWER SYSTEM.
- 2. THE SUMP PUMP DISCHARGE SHALL BE DESIGNED WITH A MINIMUM 2" AIR GAP ABOVE THE RECEIVING PIPE.
- 3. 4" DIA. PVC SDR 26 PIPE MAY BE CONNECTED TO PUBLIC STORM SEWER SYSTEM, SEE SUMP PUMP CONNECTION SPECIFICATIONS AND REQUIREMENTS FOR ADDITIONAL INFORMATION.
- 4. IN NO EVENT SHALL THE SUMP PUMP DISCHARGE INTO THE SANITARY SEWER SYSTEM.
- 5. A PERMIT IS REQUIRED PRIOR TO ANY CONNECTION, A PLAT OF SURVEY SHALL BE INCLUDED WITH THE PERMIT APPLICATION SHOWING THE POINT OF DISCHARGE AND CONNECTION TO THE STORM SEWER, THE SITE PLAN SHALL ALSO INCLUDE PIPE SPECIFICATIONS AND INVERT ELEVATIONS, CALL THE CITY 24 HOURS IN ADVANCE TO SCHEDULE AN INSPECTION.
- 6. IN AREAS WHERE NO REAR YARD STORM SYSTEMS ARE PRESENT, A SUMP PUMP DISCHARGE LINE MUST TERMINATE A MINIMUM OF TEN FEET FROM THE SIDE AND REAR PROPERTY LINES AND BE DIRECTED TO THE REAR SWALE.



CITY OF ST. CHARLES
ILLINOIS • SINCE 1834
Pride of the Fox

SUMP PUMP DISCHARGE CONNECTION	
DATE: 5-12-2021	NOT TO SCALE
REVISED:	DRAWING NO. C-07