MINIMUM RESTRAINED LENGTHS (IN FEET) BACK FROM BOTH SIDES OF FITTING


Fitting type/nominal size		4 "	6"	8 "	10"	12"	16"	
90 Degree Bend		17	25	32	38	45	59	
45 Degree Bend		7	10	13	16	19	24	
22.5 Degree Bend		3	5	6	8	9	12	
11.25 Degree Bend		2	2	3	4	4	6	
Dead End		39	55	73	87	103	134	
Top Side Vertical Offset	* (45 Degree)	16	23	30	36	43	55	
Bottom Side Vertical Offs	set * (45 Degree)	4	6	8	10	11	15	
Tee Run X Branch **	6" by	1	17					
Tee Run X Branch **	8″ by	1	5	34				
Tee Run X Branch **	10" by	1	1	24	49			
Tee Run X Branch **	12″ by	1	1	15	41	65		
Tee Run X Branch **	16″ by	1	1	1	26	52	95	
Reducer ***	6″ by	28						
Reducer ***	8″ by	52	30					
Reducer ***	10" by	71	54	29				
Reducer ***	12″ by	90	75	55	51			
Reducer ***	16" by	123	113	97	94	54		

** Vertical offset with minimum 10' of solid pipe between upper and lower bend.

*** Tee with MINIMUM 10' solid pipe on both sides of run.

Number indicates length of branch to be restrained.

*** Length back from Large Eng of Reducer.



CITY OF ST. CHARLES
ILLINOIS • SINCE 1834
Pride of the Fox

WATER MAIN RESTRAINT

DATE: 5-12-2021	NOT TO SCALE
REVISED:	DRAWING NO. B-09