


NOTES:

1. PLACEMENT OF PCC AND PAVING BRICKS SHALL BE DONE IN PHASES TO ENSURE THAT STREET IS OPEN TO TRAFFIC AT ALL TIMES UNLESS STREET CLOSURE IS PERMITTED BY THE CITY.
2. PCC SHALL CONSIST OF IDOT "SI" CONCRETE MIXTURE.
3. REFER TO IDOT STANDARD 442101-07 (CLASS B PATCHES) FOR DOWEL BAR AND JOINT DETAILS FOR PCC BASE.
4. THE SAND FOR THE BEDDING LAYER SHALL BE DELIVERED TO THE SITE A MINIMUM OF 24 HOURS PRIOR TO PLACEMENT TO ALLOW FOR THE MOISTURE TO DRAIN FROM THE MATERIAL.
5. THE SAND BED SHALL BE COMPACTED PRIOR TO PLACEMENT OF THE PAVER BRICKS. DISTURBED AREAS OR SCREEDED AREAS LEFT OVERNIGHT SHALL BE REMOVED AND RESCREED. FOLLOWING THE PLACEMENT OF THE PAVER BRICKS, FA-1 SAND SHALL BE SPREAD ACROSS THE SURFACE OF THE PAVERS AND COMPACTED WITH A VIBRATORY PLATE COMPACTOR.
6. THE BASE COURSE SHALL BE CONSTRUCTED OF CA-6 MATERIAL COMPACTED IN TWO LIFTS.
7. EDGE RESTRAINT SHALL BE PROVIDED ON ALL SIDES OF THE PAVER CONSTRUCTION IN THE FORM OF STANDARD CURB AND GUTTER, SIDEWALK, OR PCC BAND BORDER.
8. UNDERCUTS AND THE CONSTRUCTION OF A SUBBASE SHALL OCCUR AS NECESSARY.



CITY OF ST. CHARLES
 ILLINOIS • SINCE 1834
Pride of the Fox

BRICK PAVING IN ROADWAY

DATE: 5-12-2021

NOT TO SCALE

REVISED:

DRAWING NO. E-11