

**AGENDA ITEM EXECUTIVE SUMMARY**

Agenda Item number: 5.j

Title:

Recommendation to Approve the Award of a 2019 Peterbilt Model 348 Tandem Axle chassis to JX Peterbilt and Body to Monroe Truck Equipment and to Sell the Replacement Vehicle 2006 IHC 7400 SFA 4x2, Vehicle #1724 via an online auction to the highest bidder.

Presenter:

Michael Shortall

Meeting: Government Services Committee

Date: June 25, 2018

Proposed Cost: \$ 148,354.00

Budgeted Amount: \$ 180,000.00

Not Budgeted: ☐**Executive Summary** (*if not budgeted please explain*):

Staff is seeking approval to purchase a new 2019 Peterbilt Model 348 Tandem axle chassis from JX Peterbilt and 15' Crysteel Stainless Steel dump body with reversible plow from Monroe Truck Equipment for use by the Environmental Services Division through the National Joint Purchasing Alliance (NJPA).

JX Peterbilt (Chassis)	91,200.14
Monroe (Body/Plow)	<u>58,404.00</u>
Total	149,604.14
Pre-Pay Discount	<u>-1,250.00</u>
Total with discount	\$148,354.14

This option was presented to the City's Fleet Committee and approved through the FY18/19 budget.

Staff is also seeking approval to sell the replacement vehicle #1724 a 2006 IHC 7400-SFA-4x2, via an online auction to the highest bidder.

Attachments (*please list*):

*Detailed list of bids obtained from 2 NJPA vendors *Resolution

Recommendation/Suggested Action (*briefly explain*):

Recommendation to approve the Award of a 2019 Peterbilt Model 348 Tandem Axle chassis to JX Peterbilt and Body to Monroe Truck Equipment and to Sell the Replacement Vehicle 2006 IHC 7400 SFA 4x2, Vehicle #1724 via an online auction to the highest bidder.



QUOTATION
Monroe Truck Equipment
1051 W 7th Street
Monroe, WI 53566
Phone: 608-329-8383
Fax: 608-329-8521
Email: treynolds@monroetruck.com
www.monroetruck.com

Quote Number: 9TRR001703
Job Order Number:
Quote Date: 5/16/2018
Quote valid until: 6/15/2018
Terms: NET 30
Salesperson: SZYMCAK, STEVE
Quoted By: Tim Reynolds

Customer: ST CHARLES, CITY OF, (6948710)
ATTN: ACCOUNTS PAYABLE
ST CHARLES, IL 60174

Contact:
Phone: 630-377-4421 Fax: 630-377-4487
Email:

Dealer Code: _____
P.O. Number: _____

REASSIGN (Required for pool units): ☐ Fleet ☐ Retail

MSO/MCO (ONLY check if legally required): ☐ MSO ☐ MCO

Accepted by: _____

Date: _____

Customer must fill out the information above before the order can be processed.

Chassis Information

Year:	Make:	Model:	Chassis Color:	Cab Type:
Single/Dual: DRW	CA: CT:	Wheelbase: Engine: DIESEL	F.O. Number #:	Vin:

Monroe Truck Equipment, Inc. is pleased to offer the following quote for your review:

DESCRIPTION

AMOUNT

15' 10-15 YARD CRYSTEEL STAINLESS STEEL GLADIATOR DUMP BODY

- SIDES: 34", 7GA STAINLESS STEEL
- FRONT: 54", 7GA STAINLESS STEEL
- REAR: 44", 7GA STAINLESS STEEL
- FLOOR: 1/4" AR400, 9" RADIUS
- WESTERN UNDERSTRUCTURE
- 3/8" X 1 1/2" FLAT WALK RAIL BOTH SIDES
- SLIDE OUT/FOLD DOWN LADDER; NORTH DAKOTA LADDER
- DUMP BODY VIBRATOR - ELECTRIC - INSTALLED ON CROSSMEMBERLESS BODY
- CUSTOM STAINLESS STEEL CABSHIELD WITH INCORPORATED TARP HOUSING
- AIR TAILGATE, ELECTRIC
- 12" X 3/16" BOLT ON STAINLESS STEEL SPILL SHIELD
- SPRING LOADED SHOVEL HOLDER; STAINLESS STEEL
- SLOP LOCKS / TURNBUCKLES ON TAILGATE
- ONE PAIR 15' UNPAINTED OAK SIDE BOARDS; INCLUDES CENTER SUPPORT
- REFLECTIVE TAPE ACROSS THE BACK OF THE CAB AND SIDES OF BODY
- SELF ADJUSTABLE 87-107 DB BACKUP ALARM
- RECESSED LED S/T/T AND BACKUP LIGHTS WITH SEALED WIRE HARNESS
- RUBBER REAR FLAPS
- BARE STAINLESS STEEL FINISH

CRYSTEEL M63138 MARATHON INVERTED TELESCOPIC HOIST

- 37.4 TON CAPACITY
- 2000 P.S.I.
- DOUBLE ACTING

AERO 575 ELECTRIC TARP SYSTEM FOR DUMP BODY

- ELECTRIC
- ASPHALT COVER
- CUSTOM INSTALLATION TO BE RECESSED IN BULKHEAD / CABSHIELD

PINTLE HOOK W/MOUNTING, 50 TON, TANDEM AXLE

- PREMIER 2200 PINTLE HOOK
- ELECTRIC BRAKE CONTROL
- 7-WAY CONNECTOR, ROUND SOCKET, ROUND PIN

WHELEN ILL DOT STATE SPEC 72"

- 72" JUSTICE LED LIGHT BAR MOUNTED ON ROOF
- REAR BODY LED STROBES MOUNTED IN CORNER POST
- LED S/T/T MOUNTED IN REAR POST, PINTLE PLATE AND ON TOP OF CAB SHIELD
- LED BACK UP LIGHT MOUNTED IN REAR CORNER POST
- 2 AMBER AND 1 CLEAR STORBE INSTALLED OUTSIDE THE CORNER POST ON EACH SIDE
- SCENE LIGHTS ADDED TO ILLINOIS LIGHTBAR
- 2-YEAR WARRANTY

DESCRIPTION	AMOUNT
HYDRAULIC PACKAGE, 3-BANK VALVE W/MANIFOLD, TANK, & MISC. COMPONENTS, HIGH FLOW HOIST	
- HOT SHIFT PTO	
- TXV92 PUMP	
- SECTIONAL VALVE W/SPREADER MANIFOLD	
- HOIST: 4 WAY/3POS, W/500 PSI A PORT RELIEF, 40 GPM, MANUAL	
- LOAD SENSE MID-INLET SECTION, 2500 PSI MAIN RELIEF	
- PLOW LIFT: 4 WAY/3POS, 20 GPM, MANUAL	
- PLOW ANGLE: 4 WAY/3POS, 20 GPM, MANUAL	
- 30 GALLON SLIM-LINE MILD STEEL HYDRAULIC TANK	
- IN-TANK RETURN FILTER W/PRESSURE GAUGE	
- MORSE CONTROLS, CABLES AND CONTROL STAND	
- MILD STEEL VALVE ENCLOSURE	
 PLOW HITCH - MC7082 QUICK HITCH	
- FOLD FLAT LIFT ARM	
- 4 X 10 DA LIFT CYLINDER	
- CHEEK PLATES WITH BUMPER	
- HELLA PLOW LIGHTS MOUNTED ON HOOD	
 MONROE MP41R11-ISCT; FULL MOLDBOARD TRIP REVERSIBLE PLOW; 1650#	
- 10 GAUGE ROLL FORMED STRAIGHT MOLDBOARD	
- (6) 1/2" X 4" TAPERED, ONE-PIECE FLAME CUT RIBS	
- 2" X 3" X 3/8" TOP MOLDBOARD ANGLE	
- 4" X 4" X 3/4" BOTTOM MOLDBOARD ANGLE	
- HORIZONTAL MOLDBOARD BRACE ANGLES	
- 5/8" X 8" ONE-PIECE TOP PUNCH CUTTING EDGE	
- DUAL COMPRESSION TRIP SPRING ASSEMBLIES	
- 4" X 4" X 3/8" CROSS-TUBE SUPPORT	
- 3-1/2" X 3-1/2" X 1/2" SEMI-CIRCLE	
- (2) 3" X 10" DOUBLE ACTING POWER REVERSE CYLINDERS WITH CUSHION VALVE	
- BUILT-IN MONROE LEVEL LIFT ASSEMBLY	
- MOLDBOARD AND PUSHFRAME 100% CONTINUOUSLY WELDED	
- MOLDBOARD POWDER COATED ORANGE	
- PUSH FRAME POWDER COATED BLACK	
- 36" FLUORESCENT ORANGE FLEXIBLE PLASTIC MARKERS, INSTALLED	
- SCREW ADJUSTABLE PARK JACK; S&I INSTALLED; 30#	
- MONROE MC6000 QUICK HITCH; PLOW PORTION; 175#	
- WRAP-AROUND CURB GUARD (EACH), S&I INSTALLED; 20#	
- WRAP-AROUND CURB GUARD (EACH), S&I INSTALLED; 20#	
- 11' RUBBER SNOW DEFLECTOR, 12", S/I INSTALLED	
- MAILBOX CUTOOT ON CURBSIDE ONLY	
 Quote Total:	\$58,404.00

Additional Options:

DESCRIPTION	AMOUNT	ADD TO QUOTE Yes / No
-------------	--------	--------------------------

Notes:

- ◆ Terms are Due Upon Receipt unless prior credit arrangements are made at the time of order.
- ◆ Please note if chassis is furnished, it is as a convenience and terms are Net Due on Receipt of Chassis.
- ◆ State and Federal taxes will be added where applicable. **Out-of-state municipal entities may be subject to Wisconsin sales tax.**
- ◆ Restocking fees may be applicable for cancelled orders.



535 East South Frontage Road, Bolingbrook, IL 60440



Date: April 24, 2018

To: Mike Shortall
City of St. Charles
200 Devereaux Way
St. Charles, IL. 60174



Dear Mike,

JX Peterbilt - is pleased to present a price quotation for (1) New 2019 Peterbilt Model 348 Tandem Axle cab and chassis with the enclosed specifications.

**Peterbilt Cab & Chassis
All as per attached specifications**

<i>2019 Peterbilt 348 tandem axle with enclosed specifications - reference WA5025</i>	<i>\$ 89,200.14</i>
<i>Doc Fees/Title fees</i>	<i>Included</i>
<i>Heated Winsheild</i>	<i>\$ 750.00</i>
<i>Flooring (can be removed with early chassis payoff)</i>	<i>\$ 1,250.00</i>
Total	\$ 91,200.14.00

Sincerely,

Tor Michael William Larkin | Sales Executive
JX Enterprises, Inc
Office: 630-970-2700 Ext 3434 | Cell: 224-200-2483
tlarkin@jxe.com | **Your Partner for the Long Haul**

535 E. South Frontage Rd, Bolingbrook, IL 60440
Business 708-889-4686 Fax 708-889-4670

Visit us at
www.JXE.com

TANDEM



JX Peterbilt TL P128
535 E South Frontage Road
Tor Larkin
Sales Executive
Bolingbrook, Illinois United States 60440
Phone:
Fax:
Email: tlarkin@jxe.com

St. Charles, City of
200 Devereaux ay

St Charles, Illinois United States 60174
Phone:
Fax:
Contact Email:
Prepared for:

Vehicle Summary

Unit		Chassis	
Model:	Model 348	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs)	40000
Description:	St charles -- tandem 348	G.C.W. (lbs):	60000
Application		Road Conditions:	
Intended Serv.:	Snowplow	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
Body		Class C (Off-Hwy)	0
Type:	End Dump	Class D (Off-Road)	0
Length (ft):	14	Maximum Grade:	6
Height (ft):	11.0	Wheelbase (in):	190
Max Laden Weight (lbs):	4200	Overhang (in):	74.79999
Trailer		Fr Axle to BOC (in):	69.8
No. of Trailer Axles:	0	Cab to Axle (in):	120.2
Type:		Cab to EOF (in):	195.0
Length (ft):	0	Overall Comb. Length (in):	330
Height (ft):	0.0	Special Req.	
Kingpin Inset (in):	0	United States Registry	
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
 Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 4/24/2018 10:52:13 AM
 Effective Date: Jul 1, 2017
 Prepared by: Tor MW Larkin

Incomplete

Model Number: Model 348
 Quote/DTPO/CO: Q14412172
 Version Number: 35.20



JX Peterbilt TL P128
535 E South Frontage Road
Tor Larkin
Sales Executive
Bolingbrook, Illinois United States 60440
Phone:
Fax:
Email: tlarkin@jxe.com

St. Charles, City of
200 Devereaux ay
St Charles, Illinois United States 60174
Phone:
Fax:
Contact Email:
Prepared for:

Description		Weight
Base Model		
Model 348 The Model 348 was designed to exceed the rigid demands of Class 7 and Class 8 specialty application markets that require rugged durability and a wide range of optional content. The Model 348 represents a multi-dimensional performer with a GVW from 33,000 to 66,000 lbs. and optional capacity ratings to suit almost any vocation. The 348 is also available in a specifically designed all-wheel-drive configuration. From construction and crane service to utility and delivery services in both Class 7 and Class 8 markets, the 348 is in a class by itself.		10,610
Other Commodity		0
Snowplow Truck which is configured for mounting a snowplow to the front. May also have dump or other body.		0
End Dump		0
United States Registry		0
Configuration		
Not Applicable Secondary Manufacturer		0
Frame & Equipment		
11-5/8in Steel Rails to 444in 11.625 x 3.874 x .375 Dimension, 2,568,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 21.4 cubic inches. Weight: 1.91 lbs/inch pair		584
190in Wheelbase		0
Three-Piece Crossmembers		0
27.8in Bumper Extension without Adapter Includes Stationary Grille. Requires FEPTO Bumper.		0
EOF Square without Xmbr For use with body builder installed crossmember.		0
Omit Rear Mudflaps and Hangers		0

Front Axle & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 4/24/2018 10:52:13 AM
Effective Date: Jul 1, 2017
Prepared by: Tor MW Larkin

Incomplete

Model Number: Model 348
Quote/DTPO/CO: Q14412172
Version Number: 35.20



Description	Weight
Dana Spicer D2000F 20,000 lb, 3.5 in. Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	152
Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	189
Power Steering Sheppard HD94 Dual For use with 16,000 to 20,000 lb. axle ratings.	0
Power Steering Reservoir Frame Mounted w/Cooler	2
PHP10 Iron PreSet Hubs	0
Bendix Air Cam Front Drum Brakes 16.5x6 Includes automatic slack adjusters & outboard mounted brake drums.	0
Dust Shields, Cam Brakes, Front Axle	4
Gusseted Cam Brackets, Steer Axle	0

Rear Axle & Equipment

Meritor MT40-14X 40,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	2,025
PHP10 Iron PreSet Hubs	0
Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	0
Dust Shields For Cam Brakes, Drive Axle(s)	15
Heavy Wall, Drive Axle(s)	88
Gusseted Cam Brackets, Drive Axle(s)	2
SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
Stability System Not Selected or Not Available	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/24/2018 10:52:13 AM	Incomplete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q14412172
Prepared by:	Tor MW Larkin		Version Number:	35.20



Description	Weight
Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0
Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
Bendix Air Cam Rear Drum Brakes 16.5x7 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
Tandem Drive Axle (Model 348)	0
Ratio 6.83 Rear Axle	0
Peterbilt Air Trac 40,000 lbs, 52in Axle Spacing Light Weight	495
Air Springs, Internal Bumpers Air Trac / Air Leaf suspensions	0
Dash Mtd Dump Switch With Indicator Light For suspension	2

Engine & Equipment

PACCAR PX-9 300@2000 GOV@2200 860@1300	0
Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.	
N21320 N205 120..Standard Maximum Speed Limit [LSL]	
N21330 N207 0....Expiration Distance	
N21340 P005 120..Hard Maximum Speed Limit	
N21350 P001 60...Maximum Accelerator Pedal Vehicle Speed	
N21360 P110 0....Accelerator Lower Droop	
N21370 P059 64...Maximum Cruise Speed	
N21380 P111 0....Cruise Control Lower Droop	
N21400 N203 252..Reserve Speed Function Reset Distance	
N21410 N202 0....Maximum Cycle Distance	
N21420 N206 10...Maximum Active Distance	
N21430 N201 0....Reserve Speed Limit Offset	
N21440 P015 NO...Engine Protection Shutdown	
N21450 P026 NO...Gear Down Protection	
N21460 P046 1400.Max PTO Speed	
N21470 P062 NO...Cruise Control Auto Resume	
N21480 P068 NO...Auto Engine Brake in Cruise	
N21500 N209 0....Expiration Distance	
N21510 P520 YES..Enable Idle Shutdown Park Brake Set	
N21520 P030 5....Timer Setting	
N21530 P233 YES..Enable Impending Shutdown Warning	

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/24/2018 10:52:13 AM	Incomplete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q14412172
Prepared by:	Tor MW Larkin		Version Number:	35.20



Description		Weight
N21540 P234 60...Timer For Impending Shutdown Warning		
N21550 P516 35...Engine Load Threshold		
N21570 P031 NO...Idle Shutdown Manual Override		
N21590 P230 YES...Enable Hot Ambient Automatic Override		
N21610 P172 40...Low Ambient Temperature Threshold		
N21630 P171 80...High Ambient Temperature Threshold		
Engine Idle Shutdown Timer Disabled		0
Eff EIST NA Expiration Miles		0
Effective VSL Setting NA		0
Belly Pan		35
CARB Engine Idling Compliance		0
PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.		
PACCAR 160 Amp Alternator, Brushed		0
Immersion Type Block Heater 110-120V		2
Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.		
PACCAR 12V Starter		0
3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA		62
Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.		
Battery Jumper Terminal Mounted Under Hood		4
LH Frame Rail. Not available with PX-7 engines.		
Kissling Battery Disconnect Switch		3
Mounted on battery box		
2-Speed Fan Clutch For Frequent Start/Stops		0
18.7 CFM Air Compressor		0
N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.		
Spin-On Fuel/Water Separator		0
No Fluid Heat Option for Fuel Filter		0
12V Heat for Fuel Filter		0
Engine Protection Shutdown		0
Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.		

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/24/2018 10:52:13 AM	Incomplete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q14412172
Prepared by:	Tor MW Larkin		Version Number:	35.20



Description	Weight
High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0
Radial Seal, Dry Type Air Cleaner, Frontal Air intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
Exhaust Single RH Side Of Cab DPF/SCR RH Under Cab (2017).	29
Curved Tip Standpipe(s)	0
18in Ht, 5In Dia Chrome, Clear Coat Standpipe(s)	-2
Transmission & Equipment	
Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.03)	110
1710 HD Driveline, 1 Midship Bearing	0
Allison FuelSense Basic Includes 5th Generation Controls, EcoCal and Dynamic Shift Sensing. For additional information see Product Portfolio.	0
Auto Neutral Activates With Parking Brake	0
Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions	0
Dash Mounted Push Button Shifter Available with Allison Transmissions.	0
Air & Trailer Equipment	
Bendix AD-IS Air Dryer W/Heater And Coalescing Filter	0
Pull Cords All Air Tanks	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/24/2018 10:52:13 AM	Incomplete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q14412172
Prepared by:	Tor MW Larkin		Version Number:	35.20



Description		Weight
Nylon Chassis Hose		0
Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.		0
High Mount Air Tanks BOC/BOS Where Possible Subject to frame review.		0
7-Way Electric Harness with Socket Mounted EOF		11
Tires & Wheels		
FF: BR 20ply 315/80R22.5 M860A		92
Diameter = 42.8 inches; SLR = 19.9 inches		
RR: BR 16ply 11R22.5 M799		72
Diameter = 42.0 inches; SLR = 19.5 inches		
Code-rear Tire Qty 08		0
FF: Accur Stl Armor 29300PK 22.5X9.00		88
Heavy Duty. PHP10-5 Hand Holes		
RR: Accur Stl Armor 50291PK 22.5X8.25		136
Heavy Duty, Two Hand Holes		
Code-rear Rim Qty 08		0
Fuel Tanks		
26in Aluminum 70 Gallon Fuel Tank LH U/C		11
Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.		
Location LH U/C 70 Gallon		0
DEF Tank Mounted LH BOC		0
Models 210, 220 and 320 mounted LH cab fender.		
Standard DEF To Fuel Ratio 2:1 Or Greater		0
DEF Tank Small		0
Battery Box & Bumper		
Aluminum Space Saver Battery Box RH BOC		-84
Battery access from side N60100 Battery Box to be BOC Position N60110 number 2 as fas to tire as N60120 possible		
Rubber Battery Pad In Bottom Of (1) Battery Box		2
Mat in box that holds batteries only		

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/24/2018 10:52:13 AM	Incomplete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q14412172
Prepared by:	Tor MW Larkin		Version Number:	35.20



Description		Weight
Aftertreatment RH U/C ALUMINUM Non-Slip Cab Entry		0
Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic.		
Steel Bumper Swept Back Painted Black, With FEPTO		90
(2) Tow pin holes and step plates on top of bumper		
Cab & Equipment		
Alum Cab 108in BBC Metton Hood w/Bright Crown		0
Includes view window RH door and convex mirror over RH door.		
Severe Service Cab Package #1		39
Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.		
Thermal Insulation Package in Cab		2
Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.		
Rubber Fender Lips 2 Inch Wide		8
Peterbilt UltraRide Driver Seat		0
Peterbilt UltraRide Passenger Seat		0
Drivers Armrest - RH Only		2
Required in Model 587 with Evolution LX seats. Optional with Evolution ST and Rolltek Seats.		
Passenger Armrest - LH only		2
Required with Evolution LX seats, optional with Evolution ST Seats.		
Black Seat Color ipo Standard Color		0
Air Ride Driver		0
High Back Driver		0
Vinyl Driver		0
Non-Air Ride Passenger		0
High Back Passenger		0
Vinyl Passenger		0
Adjustable Steering Column - Tilt/Telescope		11
Steering Wheel with Peterbilt Logo		0
Steering Wheel with embossed Peterbilt logo over horn button.		
Interior Grey/Black		0
Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.		
Day Cab Rear Window		0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 4/24/2018 10:52:13 AM
Effective Date: Jul 1, 2017
Prepared by: Tor MW Larkin

Incomplete

Model Number: Model 348
Quote/DTPO/CO: Q14412172
Version Number: 35.20



Description	Weight
One Piece Curved Windshield	0
Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper or furnished by owner sleeper.	4
Stainless Steel Mirrors 7x16 with Heat Element Right Click on Option to see Picture in Product Portfolio.	2
Power Package Includes power door locks and power windows.	0
(1) Air Horn 15in Painted Mounted under cab.	8
Standard Speaker Package For Cab (2) Speakers	4
ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	10
CB Terminals/Wiring Mtd Under Header	0
Radio Antenna Mounted on RH Mirror Bracket	0
Plug-In Auto Reset Circuit Breaker In place of fuses in junction box.	0
Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
CabMate Cab Air Suspension Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	15
Main Transmission Oil Temperature Gauge Located in Driver Information Display	0
Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall.	0
(2) Additional Electric Switches Without Wiring	0
Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 4/24/2018 10:52:13 AM
Effective Date: Jul 1, 2017
Prepared by: Tor MW Larkin

Incomplete

Model Number: Model 348
Quote/DTPO/CO: Q14412172
Version Number: 35.20



Description		Weight
Headlights Composite Fender Mounted		0
Integral park, turn, and side marker		
(5) Marker Lights, Aero LED		0
Light Emitting Diodes		
(2) Addl Dome/Reading Lights, Ceiling Mounted		0
Incandescent Square Stop/Turn/Tail/Backup		0
LH/RH Square EOF or Dropped A-Brace		
Paint		
Standard Paint Color Selection		0
(1) Color Axalta Two Stage - Cab/Hood		0
Base Coat/Clear Coat		
N85020 A - L0006EY WHITE		
N85400 HOOD TOP L0006EY WHITE		
N85500 CAB ROOF L0006EY WHITE		
N85200 FRAME N0001EA BLACK		
N85700 BUMPER N0001EA BLACK		
N85300 FENDER L0006EY WHITE		
Options Not Subject To Discount		
Peterbilt Class 7 Standard Coverage		0
1 year/Unlimited Miles/km		
PACCAR PX-9 Standard Coverage		0
2 yrs/250,000 mi (402,336 km)/6,250 hrs		
Miscellaneous		
2017 EPA Emissions Engine		0
Warranty Only		
Body company needs by October 1		
Peterbilt NJPA Program Code		0
Presentation Created Using Featured Spec		0
For Model		
Total Weight		14936

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/24/2018 10:52:13 AM	Incomplete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q14412172
Prepared by:	Tor MW Larkin		Version Number:	35.20