

	HISTORIC PRESERVATION COMMISSION AGENDA ITEM EXECUTIVE SUMMARY			
	Agenda Item Title/Address:	COA: 100 W. Main St. – Hotel Baker		
	Proposal:	Window reglazing and repainting		
	Petitioner:	Joe Salas, Hotel Baker		
Please check appropriate box (x)				
	PUBLIC HEARING		MEETING 5/21/14	X
AGENDA ITEM CATEGORY:				
X	Certificate of Appropriateness (COA)		Façade Improvement Plan	
	Preliminary Review		Landmark/District Designation	
	Discussion Item		Commission Business	
ATTACHMENTS:				
Quote for window reglazing and repainting				
EXECUTIVE SUMMARY:				
<p>The Commission recommended approval of a Façade Improvement Grant for this project on 5/7/14, with a condition that the applicant return for a COA before starting the work. The grant is scheduled to be approved by the City Council on 5/19/14.</p> <p>The Commission wanted to discuss with the owner or contractor what was causing the glazing to fail to ensure the issue would be corrected.</p> <p>Representatives of the Hotel Baker will attend the meeting.</p>				
RECOMMENDATION / SUGGESTED ACTION:				
Provide feedback and recommendations on the COA.				

K & J Painting, Inc.
732 North Street
Geneva, IL 60134-1358
Phone: 630-404-2662
Cell: 262-945-2020

BID PROPOSAL

PROJECT: Hotel Baker – St. Charles

Date: 4-11-13

Plan Date: None

Includes: Addendum 0

Painting: 09900

Base Bid: \$ 29,120.00 †
↙

Alt \$40.00 EACH To replace broken panes.

Includes: South and East Elevation (Rt 64 and River Side) Scrape old glaze out and re-glaze windows (approx 50%) where needed. Prime and Paint. This includes lifts, permits etc.

Due to limited amount of space, only one lift will be used giving a time frame of 4-5 weeks, Monday thru Friday, for completion. (After talking with the city, weekends are not an option due to events).

Sidewalks will be blocked with co-ordination with the city of St. Charles. Access to front of hotel will remain open for patrons.

If you have any questions regarding the above, please feel free to contact me on my cell phone.

Sincerely,

Jay Trapp



SHERWIN-WILLIAMS
2406 W MAIN ST
ST CHARLES, IL 60175
(630) 444-1425

04/11/2014

K & J PAINTING AND DRYWALL
732 NORTH ST
GENEVA IL 601341358

Re: Submittal for Hotel Baker

Dear Jay Trapp:

Thank you for considering Sherwin-Williams products for the Hotel Baker project. Included in this package is the Sherwin-Williams submittal for the above referenced project.

We would be willing to offer a 5 year Materials only warranty with 2 Coats of the Shercryl over the ProCryl

Should you require assistance or have any questions or concerns, please contact me at (630) 461-6178 or e-mail me at swrep6888@sherwin.com.

Sincerely,

ERIC PRESTER
Sherwin-Williams
Sales Representative



SCHEDULE

Exterior Finishes

Aluminum and Steel Frames

Primer: B66W00310 - Pro Industrial Pro-Cryl® Universal Acrylic Primer Off White

Topcoat: B66W00351 - Sher-Cryl HPA High Performance Acrylic Semi-Gloss Coating Extra White

END OF SECTION



SURFACE PREPARATION

1) Previously Coated Surfaces

Maintenance painting will frequently not permit or require complete removal of all old coatings prior to repainting. However, all surface contamination such as oil, grease, loose paint, mill scale, dirt, foreign matter, rust, mold, mildew, mortar, efflorescence, and sealers must be removed to assure sound bonding to the tightly adhering old paint. Glossy surfaces of old paint films must be clean and dull before repainting. Thorough washing with an abrasive cleanser will clean and dull in one operation, or, wash thoroughly and dull by sanding. Spot prime any bare areas with an appropriate primer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system. Check for compatibility by applying a test patch of the recommended coating system, covering at least 2 to 3 square feet. Allow to dry one week before testing adhesion per ASTM D3359. If the coating system is incompatible, complete removal is required.

END OF SPECIFICATION

Data Pages



PRO INDUSTRIAL™

113.05

PRO-CRYL® UNIVERSAL PRIMER B66-310 SERIES

As of 02/01/2014, Complies with:			
OTC	Yes	LEED® 09 CI	Yes
SCAQMD	Yes	LEED® 09 NC	Yes
CARB	Yes	LEED® 09 CS	Yes
CARB SCM 2007	Yes	LEED® 09 S	Yes
MPI#	Yes	NGBS	Yes

CHARACTERISTICS

Pro Industrial Pro-Cryl Universal Primer is an advanced technology, self cross-linking acrylic primer. It is rust inhibitive and designed for both construction and maintenance applications. It can be used as a primer under water-based or solvent-based high performance topcoats.

- Rust inhibitive
- Single component
- Early moisture resistant
- Fast dry
- Low temperature application 40°F
- Interior and exterior use
- Suitable for use in USDA inspected facilities

Color: Off White, Gray, Red Oxide

Recommended Spread Rate per coat:

Wet mils:	5.0 - 10.0
Dry mils:	2.0 - 4.0
~Coverage:	156 - 312 sq ft/gal approximate

NOTE: Brush or roll application may require multiple coats to achieve maximum film thickness and uniformity of appearance.

Drying Time @ 6.0 mils wet 50% RH:

40°F 77°F 120°F

To touch: 2 hrs 40 min 20 min

Tack free: 8 hrs 2 hrs 1 hr

To recoat: 16 hrs 4 hrs 2 hrs

To cure: 45 days 30 days 14 days

Drying time is temperature, humidity, and film thickness dependent.

Finish: Low sheen

Flash Point: N/A

Shelf Life: 36 months, unopened
Store indoors at 40°F to 100°F.

Tinting: Do not tint
B66W310 (may vary by color)

VOC (less exempt solvents):
96 g/L; 0.80 lb/gal

As per 40 CFR 59.406 and SOR/2009-264, s.12

Volume Solids: 36% ± 2%

Weight Solids: 49% ± 2%

Weight per Gallon: 10.2 lb

RECOMMENDED SYSTEMS

Waterborne topcoat:

- 1-2 cts. Pro Industrial High Performance Acrylic
- or Pro Industrial Waterborne Catalyzed Epoxy
- or Pro Industrial Multi-Surface Acrylic
- or Pro Industrial Hi-Bild Waterbased Epoxy
- or Pro Industrial Pre-Catalyzed Epoxy

Solvent borne topcoat:

- 1-2 cts. Pro Industrial High Performance Epoxy
- or Pro Industrial Urethane Alkyd

Pro Industrial Pro-Cryl Universal Primer B66W310 Off White is GREENGUARD GOLD certified for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

System Tested: (unless otherwise indicated)

- Substrate: Steel
- Surface Preparation: SSPC-SP10
- 1 ct. Pro Industrial Pro-Cryl Universal Primer
- 1 ct. Pro Industrial High Performance Acrylic

Adhesion:

- Method: ASTM D4541
- Result: 500 psi

Result: Passes

Moisture Condensation Resistance:

- Method: ASTM D4585, 100°F, 1250 hours

Result: Passes

Corrosion Weathering:

- Method: ASTM D5894, 10 cycles, 3360 hours
- Result: Passes

Pencil Hardness:

- Method: ASTM D3363
- Result: H

Direct Impact Resistance:

- Method: ASTM D2794
- Result: >140 in. lbs.

Salt Fog Resistance:

- Method: ASTM B117, 1250 hours
- Result: Passes

Dry Heat Resistance*:

- Method: ASTM D2485
- Result: 200°F

Provides performance comparable to products formulated to federal specification: AA50557 and Paint Specification: SSPC-Paint 23.

Flexibility:

- Method: ASTM D522, 180° bend, 1/4" mandrel

*Suitable for intermittent dry heat resistance up to 300°F when used as a system with Sher-Cryl HPA

PRO INDUSTRIAL™
PRO-CRYL® UNIVERSAL PRIMER



SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Do not use hydrocarbon solvents for cleaning.

Iron and Steel - Minimum surface preparation is Hand Tool Cleaning per SSPC-SP2. Remove all oil and grease from the surface per SSPC-SP1. For better performance, use Commercial Blast Cleaning per SSPC-SP6.

Aluminum - Remove all oil, grease, dirt, oxide and other foreign material per SSPC-SP1.

Galvanizing - Allow to weather a minimum of six months prior to coating. Solvent Clean per SSPC-SP1. When weathering is not possible, or the surface has been treated with chromates or silicates, first Solvent Clean per SSPC-SP1 and apply a test patch. Allow paint to dry at least one week before testing adhesion. If adhesion is poor, brush blasting per SSPC-SP7 is necessary to remove these treatments. Rusty galvanizing requires a minimum of Hand Tool Cleaning per SSPC-SP2, prime the area the same day as cleaned.

Previously Painted Surfaces - If in sound condition, clean the surface of all foreign material. Smooth, hard or glossy coatings and surfaces should be dulled by abrading the surface. Apply a test area, allowing paint to dry one week before testing adhesion. If adhesion is poor, additional abrasion of the surface and/or removal of the previous coating may be necessary. Retest surface for adhesion. If paint is peeling or badly weathered, clean surface to sound substrate and treat as a new surface as above.

APPLICATION

Refer to the MSDS before using

Temperature: 40°F minimum
 120°F maximum
 (air, surface, and material)
 At least 5°F above dew point

Relative humidity: 85% maximum

The following is a guide. Changes in pressures and tip sizes may be needed for proper spray characteristics. Always purge spray equipment before use with listed reducer. Any reduction must be compatible with the existing environmental and application conditions.

Reducer: Water

Airless Spray

Pressure2000 psi
 Hose 1/4" ID
 Tip015" - .019"
 Filter 60 mesh
 ReductionNot recommended

Conventional Spray

Gun Binks 95
 Fluid Nozzle..... 66
 Air Nozzle 63PB
 Atomization Pressure60 psi
 Fluid Pressure25 psi
 ReductionAs needed up to 5% by volume

Brush Nylon/Polyester
 ReductionNot recommended

Roller3/8" woven
 ReductionAs needed up to 5% by volume

If specific application equipment is listed above, equivalent equipment may be substituted.

CLEANUP INFORMATION

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with Mineral Spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using Mineral Spirits.

HOTW 02/17/2014 B66W310 32 96

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Information and Application Bulletin. The Sherwin-Williams Company warrants our products to be free of manufacturing defects in accord with applicable Sherwin-Williams quality control procedures. Liability for products proven defective, if any, is limited to replacement of the defective product or the refund of the purchase price paid for the defective product as determined by Sherwin-Williams. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SHERWIN-WILLIAMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Protective & Marine Coatings

SHER-CRYL™ HPA HIGH PERFORMANCE ACRYLIC

B66-300 SERIES
B66-350 SERIES

GLOSS
SEMI-GLOSS

Revised: March 27, 2014

PRODUCT INFORMATION

1.26

PRODUCT DESCRIPTION

SHER-CRYL HPA is a new technology, ambient cured, one component acrylic coating with superior exterior performance properties. Provides performance comparable to high performance solvent based coatings such as urethanes and epoxies.

- Chemical resistant
- Superior color and gloss retention
- Outstanding early moisture resistance
- Flash rust/early rust resistant
- Low odor, low VOC
- Corrosion resistant
- Fast dry
- Outstanding application characteristics

PRODUCT CHARACTERISTICS

Finish:	High Gloss or Semi-Gloss
Color:	Wide range of colors available
Volume Solids:	38.5% ± 2%, Ultra White
Weight Solids:	51% ± 2%, Ultra White
VOC (EPA Method 24):	<200 g/L; 1.66 lb/gal

Recommended Spreading Rate per coat:

	Minimum	Maximum
Wet mils (microns)	6.0 (150)	10.0 (250)
Dry mils (microns)	2.5 (63)	4.0 (100)
~Coverage sq ft/gal (m²/L)	154 (3.8)	247 (6.0)
Theoretical coverage sq ft/gal (m²/L) @ 1 mil / 25 microns dft	616 (15.1)	

NOTE: Brush or roll application may require multiple coats to achieve maximum film thickness and uniformity of appearance.

Drying Schedule @ 7.0 mils wet (175 microns):

	@ 50°F/10°C	@ 77°F/25°C	@ 120°F/49°C
		50% RH	
To touch:	1 hour	30 minutes	5 minutes
To handle:	8 hours	5 hours	15 minutes
To recoat:	8 hours	5 hours	15 minutes
To cure:	30 days	30 days	30 days

Drying time is temperature, humidity, and film thickness dependent.

Shelf Life:	36 months, unopened Store indoors at 50°F (10°C) to 100°F (38°C)
Flash Point:	>230°F (110°C) PMCC, mixed
Reducer:	Water R8K10 - WB Hot Weather Reducer up to 10%
Clean Up:	Water

RECOMMENDED USES

For use over prepared:

- Steel
- Aluminum
- Zinc rich primers
- Galvanizing
- Concrete
- Wood
- Masonry

Examples:

- Buildings
- Machinery
- Power plants
- Select Marine Structures
- Storage Tanks
- Equipment
- Piping
- Water treatment plants
- New Construction
- Structural Steel

- Suitable for use in USDA inspected facilities
- Can be used as a dryfall coating under certain environmental conditions (see Application Bulletin)
- Conforms to AWWA D102 OCS #3
- Acceptable for use in high performance architectural applications
- Acceptable for interior use / drywall
- Conforms to MPI #'s 154 & 164 (Gloss); 141, 153, & 163 (Semi-Gloss)
- Complies with performance criteria of SSPC Paint 24.
- FIRETEX Hydrocarbon Coatings

PERFORMANCE CHARACTERISTICS

Substrate*: Steel

Surface Preparation*: SSPC-SP10

System Tested*:

2 cts. Sher-Cryl HPA @ 3.0 mils (75 microns) dft/ct
*unless otherwise noted below

Test Name	Test Method	Results
Adhesion	ASTM D4541	946 psi
Corrosion Weathering¹	ASTM D5894, 10 cycles, 3,360 hours	Rating 9 per ASTM D610 for rusting ; Rating 10 per ASTM D714 for blistering
Direct Impact Resistance	ASTM D2794	>100 in. lbs.
Dry Heat Resistance	ASTM D2485	300°F (149°C)
Exterior Durability	3 years, 45° South	Excellent
Flexibility	ASTM D522, 180° bend, 1/8" mandrel	Passes
Humidity Resistance¹	ASTM D4585, 1,250 hours	Rating 9 per ASTM D1654 for corrosion ; Rating 10 per ASTM D714 for blistering
Pencil Hardness	ASTM D3363	2B
Salt Fog Resistance¹	ASTM B117, 1,250 hours	Rating 9 per ASTM D1654 for corrosion ; Rating 10 per ASTM D714 for blistering
Thermal Cycling	ASTM D2246, 10 cycles	Passes

Footnote:

¹ 1 ct. Sher-Cryl HPA over 1 ct. Pro-Cryl Universal Primer

Provides performance comparable to products formulated to federal specification: AA50570, and Paint Specification: SSPC-Paint 23 and 24.



Protective & Marine Coatings

SHER-CRYL™ HPA HIGH PERFORMANCE ACRYLIC

B66-300 SERIES
B66-350 SERIES

GLOSS
SEMI-GLOSS

PRODUCT INFORMATION

1.26

RECOMMENDED SYSTEMS		
	Dry Film Thickness / ct.	
	Mils	(Microns)
Steel:		
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Steel:		
1 ct. Pro-Cryl Universal Primer	2.0-4.0	(50-100)
1-2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Steel:		
1 ct. DTM Acrylic Primer/Finish	2.5-5.0	(63-125)
or Kem Bond HS	2.0-5.0	(50-125)
or Zinc Clad Primer	3.0-5.0	(75-125)
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Steel:		
1 ct. Zinc Clad XI	3.0-4.0	(75-100)
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Aluminum:		
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Aluminum:		
1 ct. DTM Wash Primer	0.7-1.3	(18-32)
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Galvanizing:		
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Concrete Block:		
1 ct. Heavy Duty Block Filler	10.0-18.0	(250-450)
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Concrete/Masonry:		
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Prefinished Siding: (Baked-on finishes)		
1 ct. DTM Bonding Primer	2.0-5.0	(50-125)
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Wood, exterior:		
1 ct. A-100 Exterior Oil Wood Primer	1.5	(38)
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)
Wood, interior:		
1 ct. Premium Wall & Wood Primer	1.8	(45)
2 cts. Sher-Cryl HPA	2.5-4.0	(63-100)

The systems listed above are representative of the product's use, other systems may be appropriate.

DISCLAIMER

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Information and Application Bulletin.

SURFACE PREPARATION

Surface must be clean, dry, and in sound condition. Remove all oil, dust, grease, dirt, loose rust, and other foreign material to ensure adequate adhesion.

Do not use hydrocarbon solvents for cleaning.

Refer to product Application Bulletin for detailed surface preparation information.

Minimum recommended surface preparation:

- Iron & Steel: SSPC-SP2
- Aluminum: SSPC-SP1
- Galvanizing: SSPC-SP1
- Concrete & Masonry: SSPC-SP13/NACE 6, or ICRI No. 310.2, CSP 1-3
- * Wood: Dry and sanded smooth
- * Prefinished Siding: SSPC-SP1
- * Requires primer

Surface Preparation Standards

Condition of Surface	ISO 8501-1 BS7079:A1	Swedish Std. SIS055900	SSPC	NACE
White Metal	Sa 3	Sa 3	SP 5	1
Near White Metal	Sa 2.5	Sa 2.5	SP 10	2
Commercial Blast	Sa 2	Sa 2	SP 6	3
Brush-Off Blast	Sa 1	Sa 1	SP 7	4
Hand Tool Cleaning	C St 2	C St 2	SP 2	-
Pitted & Rusted	D St 2	D St 2	SP 2	-
Power Tool Cleaning	C St 3	C St 3	SP 3	-
Pitted & Rusted	D St 3	D St 3	SP 3	-

TINTING

Tint with EnviroToner colorants at 100% strength. Do not use BAC.

Five minutes minimum mixing on a mechanical shaker is required for complete mixing of color.

APPLICATION CONDITIONS

Temperature: 50°F (10°C) minimum, 120°F (49°C) maximum (air, surface, and material)
At least 5°F (2.8°C) above dew point

Relative humidity: 85% maximum

Refer to product Application Bulletin for detailed application information.

ORDERING INFORMATION

Packaging: 1 gallon (3.78L) and 5 gallon (18.9L) containers

Weight: 10.30 ± 0.2 lb/gal 1.24 Kg/L

SAFETY PRECAUTIONS

Refer to the MSDS sheet before use.

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams representative for additional technical data and instructions.

WARRANTY

The Sherwin-Williams Company warrants our products to be free of manufacturing defects in accord with applicable Sherwin-Williams quality control procedures. Liability for products proven defective, if any, is limited to replacement of the defective product or the refund of the purchase price paid for the defective product as determined by Sherwin-Williams. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SHERWIN-WILLIAMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Protective & Marine Coatings

SHER-CRYL™ HPA HIGH PERFORMANCE ACRYLIC

B66-300 SERIES
B66-350 SERIES

GLOSS
SEMI-GLOSS

Revised: March 27, 2014

APPLICATION BULLETIN

1.26

SURFACE PREPARATIONS

Surface must be clean, dry, and in sound condition. Remove all oil, dust, grease, dirt, loose rust, and other foreign material to ensure adequate adhesion.

Do not use hydrocarbon solvents for cleaning.

Iron & Steel

Minimum surface preparation is Hand Tool Clean per SSPC-SP2. Remove all oil and grease from surface per SSPC-SP1. For better performance, use Commercial Blast Cleaning per SSPC-SP6. Primer recommended for best performance.

Aluminum

Remove all oil, grease, dirt, oxide and other foreign material per SSPC-SP1.

Galvanizing

The surface should be weathered for 6 months prior to painting. Remove all oil and grease per SSPC-SP1. Rusty galvanizing requires a minimum of Hand Tool Cleaning per SSPC-SP2. Prime area the same day as cleaned with Pro-Cryl.

Concrete and Masonry

For surface preparation, refer to SSPC-SP13/NACE 6 or ICRI No. 310.2, CSP 1-3. Surfaces should be thoroughly cleaned and dry. Surface temperatures must be at least 55°F (13°C) before filling. If required for a smoother finish, use Heavy Duty Block Filler, B42W46. Filler must be thoroughly dry before topcoating per manufacturer's recommendations.

Weathered masonry and soft or porous cement board must be brush blasted or power tool cleaned to remove loosely adhering contamination and to get to a hard, firm surface. Apply one coat Loxon Conditioner, following label recommendations.

Wood

Surface must be clean, dry and sound. Prime with recommended primer. No painting should be done immediately after a rain or during foggy weather. Knots and pitch streaks must be scraped, sanded and spot primed before full coat of primer is applied. All nail holes or small openings must be properly caulked.

Pre-Finished Siding:

Remove oil, grease, dirt, oxides, and other contaminants from the surface by cleaning per SSPC-SP1 or water blasting per NACE Standard RP-01-72. Always check for compatibility of the previously painted surface with the new coating by applying a test patch of 2 - 3 square feet. Allow to dry thoroughly for 1 week before checking adhesion. DTM Bonding Primer is required.

Previously Painted Surfaces

If in sound condition, clean the surface of all foreign material. Smooth, hard or glossy coatings and surfaces should be dulled by abrading the surface. Apply a test area, allowing paint to dry one week before testing adhesion. If adhesion is poor, additional abrasion of the surface and/or removal of the previous coating may be necessary. Retest surface for adhesion. If paint is peeling or badly weathered, clean surface to sound substrate and treat as a new surface as above.

Surface Preparation Standards

Condition of Surface	ISO 8501-1 BS7079:A1	Swedish Std. SIS055900	SSPC	NACE
White Metal	Sa 3	Sa 3	SP 5	1
Near White Metal	Sa 2.5	Sa 2.5	SP 10	2
Commercial Blast	Sa 2	Sa 2	SP 6	3
Brush-Off Blast	Sa 1	Sa 1	SP 7	4
Hand Tool Cleaning	C St 2	C St 2	SP 2	-
Pitted & Rusted	D St 2	D St 2	SP 2	-
Rusted	C St 3	C St 3	SP 3	-
Power Tool Cleaning	D St 3	D St 3	SP 3	-

APPLICATION CONDITIONS

Temperature:	50°F (10°C) minimum, 120°F (49°C) maximum (air, surface, and material) At least 5°F (2.8°C) above dew point
Relative humidity:	85% maximum

APPLICATION EQUIPMENT

The following is a guide. Changes in pressures and tip sizes may be needed for proper spray characteristics. Always purge spray equipment before use with listed reducer. Any reduction must be compliant with existing VOC regulations and compatible with the existing environmental and application conditions.

Reducer	Water R8K10 - WB Hot Weather Reducer up to 10%
----------------------	--

Clean Up	Water
-----------------------	-------

Airless Spray

Pressure.....	1500 psi
Hose.....	1/4" ID
Tip017" - .021"
Filter.....	60 mesh
Reduction.....	Not recommended

Conventional Spray

Gun	Binks 95
Fluid Nozzle	66
Air Nozzle.....	63PB
Atomization Pressure.....	50 psi
Fluid Pressure.....	15-20 psi
Reduction.....	As needed up to 12½% by volume

Brush

Brush.....	Nylon / polyester
Reduction.....	Not recommended

Roller

Cover	3/8" woven solvent resistant core
Reduction.....	Not recommended

If specific application equipment is not listed above, equivalent equipment may be substituted.



Protective & Marine Coatings

SHER-CRYL™ HPA HIGH PERFORMANCE ACRYLIC

B66-300 SERIES
B66-350 SERIES

GLOSS
SEMI-GLOSS

APPLICATION BULLETIN

1.26

APPLICATION PROCEDURES

Surface preparation must be completed as indicated.

Mixing Instructions: Mix paint thoroughly to a uniform consistency with low speed power agitation prior to use.

Apply paint at the recommended film thickness and spreading rate as indicated below:

Recommended Spreading Rate per coat:

	Minimum	Maximum
Wet mils (microns)	6.0 (150)	10.0 (250)
Dry mils (microns)	2.5 (63)	4.0 (100)
~Coverage sq ft/gal (m ² /L)	154 (3.8)	247 (6.0)
Theoretical coverage sq ft/gal (m ² /L) @ 1 mil / 25 microns dft	616 (15.1)	

NOTE: Brush or roll application may require multiple coats to achieve maximum film thickness and uniformity of appearance.

Drying Schedule @ 7.0 mils wet (175 microns):

	@ 50°F/10°C	@ 77°F/25°C 50% RH	@ 120°F/49°C
To touch:	1 hour	30 minutes	5 minutes
To handle:	8 hours	5 hours	15 minutes
To recoat:	8 hours	5 hours	15 minutes
To cure:	30 days	30 days	30 days

Drying time is temperature, humidity, and film thickness dependent.

Application of coating above maximum or below minimum recommended spreading rate may adversely affect coating performance.

CLEAN UP INSTRUCTIONS

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with Mineral Spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using Mineral Spirits.

DISCLAIMER

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Information and Application Bulletin.

PERFORMANCE TIPS

Stripe coat all crevices, welds, and sharp angles to prevent early failure in these areas.

When using spray application, use a 50% overlap with each pass of the gun to avoid holidays, bare areas, and pinholes. If necessary, cross spray at a right angle

During the early stages of drying, the coating is sensitive to rain, dew, high humidity, and moisture condensation. Plan painting schedules to avoid these influences during the first 16-24 hours of curing.

Spreading rates are calculated on volume solids and do not include an application loss factor due to surface profile, roughness or porosity of the surface, skill and technique of the applicator, method of application, various surface irregularities, material lost during mixing, spillage, overthinning, climatic conditions, and excessive film build.

Excessive reduction of material can affect film build, appearance, and adhesion.

Application temperature above 95°F (35°C) may cause dry spray, uneven sheen, and poor adhesion.

Application temperature below 50°F (10°C) may cause poor adhesion and lengthen the drying and curing time.

Sher-Cryl Acrylic is extremely sensitive to hydrocarbon containing solvents. When cleaning the surface per SSPC-SP1, use only an emulsifying industrial detergent, followed by a water rinse. Do not use hydrocarbon containing solvents.

Do not use hydrocarbon solvents for cleaning.

Refer to Product Information sheet for additional performance characteristics and properties.

Sher-Cryl can be used as a dryfall coating in certain environmental conditions. Test product before each application. Test by spraying 15-25 feet toward paint container. All material should readily wipe clean. Temperature and humidity will affect ability to dryfall. Hot surface will cause overspray to bond to surface. Always clean overspray immediately from hot surfaces.

Refer to Product Information sheet for additional performance characteristics and properties.

SAFETY PRECAUTIONS

Refer to the MSDS sheet before use.

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams representative for additional technical data and instructions.

WARRANTY

The Sherwin-Williams Company warrants our products to be free of manufacturing defects in accord with applicable Sherwin-Williams quality control procedures. Liability for products proven defective, if any, is limited to replacement of the defective product or the refund of the purchase price paid for the defective product as determined by Sherwin-Williams. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SHERWIN-WILLIAMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.